



Adhesive, Ink & Coatings Remover

Solvent-Based • Water-Rinsable

WARNING KEEP OUT OF REACH OF CHILDREN.

See other cautions
on back/side panel

NET CONTENTS:
ONE U.S. PINT

A DIVISION OF TRION CHEMICALS®
320 37th Avenue • St. Charles, IL 60174
1-800-252-1114 • www.bradley-systems.com

Removes a wide range of adhesives, inks, coatings, greases & oils with minimal effort:

- Dissolves plastisol/oil-based/solvent-based inks
- Works on all screen/mesh types
- Quickly removes adhesives & residue
- Safe for use on all metals, ceramics, rubbers, polymers and painted surfaces
- Readily Biodegradable:
 - Non-Hazardous/High Flashpoint
 - Low-Voc/Low-Odor
 - No Sara/Prop 65 Reportable Ingredients
 - Non-Toxic, Non-Acid, Non-Caustic
 - No Chlorinated Solvents, No Petroleum Distillates
- High Solvency - Meets or Exceeds Boeing D6-17487 Revision L Spec.
- Does not evaporate - rinses clean with water or damp towel

USAGE DIRECTIONS:

Adhesive Removal: Spray directly on the adhesive to be removed and work in, being careful on painted surfaces not to scratch or mar the finish. A soft plastic scraper might be needed to lift off the adhesive. Be careful not to scratch or damage the surface with any tool. Once the adhesive is removed, simply rinse with water or wipe with a damp cloth.

Screen-Cleaning/Anilox Rollers/Blades: Spray or Pour a small amount on the screen, anilox rollers, blades, plates, or other machinery surfaces. Scrub with a dedicated nylon brush or scrub pad. On Screens, turn over and repeat on the back of screen. Rinse thoroughly with clean potable water.

Tar/Asphalt/Grease/Oil Removal: Simply spray the area to be cleaned using a low-pressure sprayer. Allow to remain on for ten or fifteen minutes and flush away with water. Use soft bristle brush for stubborn soils if necessary (only on non-painted surfaces as using a brush on painted surfaces may cause scratches). Cover any electrical contacts.

Machinery Parts: Place parts in a tank. Allow to soak for one half hour to two hours depending upon the accumulation of grease or tar on the part. Remove parts and rinse with water. A stiff bristle brush may be used for caked on grease.

WARNING: Harmful if swallowed. May cause an allergic skin reaction. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves. **IF ON SKIN:** Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. **IF SWALLOWED:** Call a poison center or doctor/physician if you feel unwell. Rinse mouth.



Dispose of contents/container to an approved waste disposal plant.

ADDITIONAL FIRST AID MEASURES:

IF IN EYES: Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.

IF INHALED: Remove to fresh air.

An SDS for this product is available. Please read the SDS carefully and follow all directions when using or handling this product. Never reuse empty containers. Incompatible materials may adversely react.

BT2000

126 Made in the U.S.A.